

UL Certification

storex®	Grade	VE-0860
----------------	-------	---------

iq.ul.com

Component - **Plastics** [\[guide info\]](#) E115797

Lotte Advanced Materials Co Ltd
56 Gosan-ro, Uiwang-si Gyeonggi-do 437-711 KR

VE-0860(+)
Acrylonitrile Butadiene Styrene (ABS), "STAREX", furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.5	V-0	1	0	95	95	95
	2.5-2.7	V-0, 5VB	1	0	95	95	95

Comparative Tracking Index (CTI): 1
 Dielectric Strength (kV/mm): -
 High-Voltage Arc Tracking Rate (HVTR): 2
 Dimensional Stability (%): -


Inclined Plane Tracking (IPT): -
 Volume Resistivity (10^x ohm-cm): -
 High Volt, Low Current Arc Resis (D495): 7

(+) - May be replaced by one, two, or three numbers and/or letter(s)

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1995-08-04
 Last Revised: 2012-12-06

© 2016 UL LLC



IEC and ISO Test Methods

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10, IEC 60695-11-20	Class (color)	1.5	V-0 (ALL)
			2.5-2.7	V-0, 5VB (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-